

ALGINE

SLI035070CW_35W

LED luminaire ALGINE, with a power of 35 W, high light efficacy 111 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for surface, recessed and suspended mounting.



Power	35 W	Voltage	230 V
Luminous flux*	3900 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20

Technical data

Code	SLI035070CW_35W
Power	35 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3900 lm (360°)
Luminous flux**	3900 lm (360°)
Lamp efficacy	111 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	25000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x10 mm
Mounting hole	600x600 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC
Catalogue number	SLI035070CW_35W

Logistics data

Bulk packaging	8 pcs.
Quantity per pallet	160 pcs.
Gross weight (1 pcs.)	2.1 kg

Related documents

 User manual Declaration of Conformity Photometric file