

111
lm/W

620
X
620




Power	35 W	Voltage	230 V
Luminous flux*	3900 lm (360°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	120 °
IK	06	Protection class	IP20



 User manual



 Declaration of Conformity



 Photometric file

SLI035070NW_35W

Technical data:

Product code	SLI035070NW_35W
Power	35 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3900 lm (360°)
Luminous flux**	3900 lm (360°)
Light efficiency	111 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	25000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	620x620x10 mm
Mounting hole	600x600 mm
For use	Inside
Assembly method	podtynkowy, natynkowy, zwieszany
Application	INT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux
Product is sold to the foreign markets. Also available as SMART, DALI, DIM.