

SLI037029NW_PW

SLI037029NW_PW

ALGINE 2IN1 SURFACE-RECESSED DOWNLIGHT 18W 1900LM NW 230V IP20 ROUND

IK06




Power	18 W	Voltage	230 V
Luminous flux*	2200 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	110 °
IK	06	Degree of protection (IP)	IP20

Technical data


Code	SLI037029NW_PW
Power	18 W
Nominal current	140 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0,5
Useful luminous flux*	2200 lm (360°)
Luminous flux**	1750 lm (360°)
Lamp efficacy	122 lm/W
Luminous intensity	670 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	223x35 mm
Mounting hole	200 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	Inside
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 3D model

