

122  
lm/W




CE

Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2200 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>110 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>



 User manual



 Declaration of Conformity



 3D model

**Technical data:**

Product code	SLI037029NW_PW
Power	18 W
Nominal current	140 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	2200 lm (360°)
Luminous flux**	1750 lm (360°)
Light efficiency	122 lm/W
Luminous intensity	670 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	223x35 mm
Mounting hole	200 mm
For use	Inside
Assembly method	natynkowy, podtynkowy
Application	Inside
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux