

ALGINE

SLI038017CCT

Smart LED luminaire ALGINE with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via the app on your mobile device. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT

IK06




Power	22 W	Voltage	230 V
Luminous flux*	2000 lm (120°)	Colour temperature	3000-6500 K
Colour of light	CCT	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20

Technical data

Code	SLI038017CCT
Power	22 W
Nominal current	180 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	22 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	2000 lm (120°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	91 lm/W
Colour temperature	3000-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	ø215x38 mm
Mounting hole	ø205 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

