

# ALGINE

SLI038020CCT

Smart LED luminaire ALGINE with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via the app on your mobile device. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT

IK06



Power	<b>22 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2000 lm (120°)</b>	Colour temperature	<b>3000-6500 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data


---

Code	SLI038020CCT
Power	22 W
Nominal current	180 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	22 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	2000 lm (120°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	91 lm/W
Colour temperature	3000-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	215x215x38 mm
Mounting hole	205X205 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC


## Related documents

---



 User manual




 Declaration of Conformity



 Photometric file



 3D model

