

# TECHNIC LAMP

SLI041044NW\_PW



See  
more

Technic luminaire TECHNIC LAMP, with a power of 8 W, high light efficacy 118 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP54

IK10



|                 |                      |                           |               |
|-----------------|----------------------|---------------------------|---------------|
| Power           | <b>8 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>940 lm (360°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b> | Beam angle                | <b>120 °</b>  |
| IK              | <b>10</b>            | Degree of protection (IP) | <b>IP54</b>   |

## Technical data

|                           |                |
|---------------------------|----------------|
| Code                      | SLI041044NW_PW |
| Power                     | 8 W            |
| Nominal current           | 65 mA          |
| Voltage                   | 230 V          |
| Energy consumption        | 8 kWh/1000h    |
| Frequency                 | 50HZ Hz        |
| Protection class          | II             |
| Useful luminous flux*     | 940 lm (360°)  |
| Luminous flux**           | 850 lm (360°)  |
| Lamp efficacy             | 118 lm/W       |
| Colour temperature        | 4000 K         |
| Colour of light           | Neutral white  |
| Beam angle                | 120 °          |
| RA                        | >80            |
| Light source included     | Yes            |
| Dimmable                  | No             |
| Working temperature range | -20/+40 °      |
| Lifespan                  | 17000 h        |
| Housing material          | PC             |
| IK                        | 10             |
| Degree of protection (IP) | IP54           |
| Colour                    | White          |
| Dimension (AxBxC)         | 157x80x46 mm   |
| For use                   | Inside/Outside |
| Assembly method           | On the ceiling |
| Made in                   | PRC            |
| Other                     | IP54 ,         |



## Related documents

[User manual](#)[Declaration of Conformity](#)[Photometric file](#)

