


IP20  
IP44



Power	<b>25 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2200 lm (90°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>100 °</b>
Protection class	<b>IP44/IP20***</b>		




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI043006WW
Power	25 W
Nominal current	180 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	2200 lm (90°)
Luminous flux**	2200 lm (360°)
Light efficiency	88 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP44/IP20***
Colour	White
Dimension (axbxc)	244x85 mm
Mounting hole	210 mm
For use	Inside/Outside
Assembly method	Recessed
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
\*\*\*Degree of protection [IP] (from the bottom/ from the top)