


IP54 125  
lm/W



CE

|                |                       |                    |               |
|----------------|-----------------------|--------------------|---------------|
| Power          | <b>12 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>1500 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour   | <b>CW</b>             | Beam angle         | <b>110 °</b>  |
| IK             | <b>6</b>              | Protection class   | <b>IP54</b>   |




See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

**Technical data:**

|                              |                |
|------------------------------|----------------|
| Product code                 | SLI043007CW_PW |
| Power                        | 12 W           |
| Nominal current              | 86 mA          |
| Voltage                      | 230 V          |
| Energy consumption           | 12 kWh/1000h   |
| Frequency                    | 50HZ Hz        |
| Protection class             | II             |
| Power factor                 | 0.6            |
| Useful luminous flux*        | 1500 lm (360°) |
| Luminous flux**              | 1100 lm (360°) |
| Light efficiency             | 125 lm/W       |
| Colour temperature           | 6000 K         |
| Light colour                 | CW             |
| Beam angle                   | 110 °          |
| RA                           | 80             |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 17000 h        |
| Housing material             | PC+PS          |
| IK                           | 6              |
| Protection class             | IP54           |
| Colour                       | White          |
| Dimension (axbxc)            | 145x34 mm      |
| Mounting hole                | 120 mm         |
| For use                      | Inside         |
| Assembly method              | Recessed       |
| Application                  | INT            |
| Made in                      | PRC            |



\*Applies to the LED source used. \*\*Luminaire luminous flux