

DURE 3

SLI043009WW_PW

Downlight luminaire DURE 3, with a power of 24 W, high light efficacy 121 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IP54

IK06



Power	24 W
Luminous flux*	2900 lm (360°)
Colour of light	WW
IK	6

Voltage	230 V
Colour temperature	3000 K
Beam angle	110 °
Degree of protection (IP)	IP54

Technical data

Code	SLI043009WW_PW
Power	24 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	2900 lm (360°)
Luminous flux**	1900 lm (360°)
Lamp efficacy	121 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	220x34 mm
Mounting hole	195 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	480 pcs.
Gross weight (1 pcs.)	0.316 kg



Related documents

 User manual Declaration of Conformity Photometric file 3D model

