

DURE 3

SLI043010NW_PW

Downlight luminaire DURE 3, with a power of 12 W, high light efficacy 125 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IP54

IK06



Power	12 W
Luminous flux*	1500 lm (360°)
Colour of light	Neutral white
IK	6

Voltage	230 V
Colour temperature	4000 K
Beam angle	110 °
Degree of protection (IP)	IP54

Technical data

Code	SLI043010NW_PW
Power	12 W
Nominal current	86 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	1500 lm (360°)
Luminous flux**	1100 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	145x145x34 mm
Mounting hole	120x120 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

Logistics data

Bulk packaging	60 pcs.
Quantity per pallet	1200 pcs.
Gross weight (1 pcs.)	0.17 kg



Related documents

 User manual Declaration of Conformity Photometric file 3D model

