

DURE 3 MAX

SLI043013CW_PW

Downlight luminaire DURE 3 MAX, with a power of 12 W, high light efficacy 133 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



IP44

IK06



Power	12 W
Luminous flux*	1600 lm (360°)
Colour of light	CW
IK	6

Voltage	230 V
Colour temperature	6000 K
Beam angle	110 °
Degree of protection (IP)	IP44

Technical data

Code	SLI043013CW_PW
Power	12 W
Nominal current	68 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.8
Useful luminous flux*	1600 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	133 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PA6+Aluminum
IK	6
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	140x30 mm
Mounting hole	110 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



Related documents



 User manual



 Photometric file

