

DURE 3 MAX

SLI043015WW_PW

Downlight luminaire DURE 3 MAX, with a power of 28 W, high light efficacy 121 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



IP44

IK06



Power	28 W
Luminous flux*	3400 lm (360°)
Colour of light	WW
IK	6

Voltage	230 V
Colour temperature	3000 K
Beam angle	110 °
Degree of protection (IP)	IP44

Technical data

Code	SLI043015WW_PW
Power	28 W
Nominal current	137 mA
Voltage	230 V
Energy consumption	28 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.8
Useful luminous flux*	3400 lm (360°)
Luminous flux**	2300 lm (360°)
Lamp efficacy	121 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PA6+Aluminum
IK	6
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	230x30 mm
Mounting hole	190 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

