

AQUATICA

SLI043016WW_PW

LED luminaire AQUATICA, with a power of 15 W, high light efficacy 120 lm/W. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for surface mounting.

IP44

Power	15 W	Voltage	230 V
Luminous flux*	1800 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	150 °
Degree of protection (IP)	IP44		

Technical data

Code	SLI043016WW_PW
Power	15 W
Nominal current	115 mA
Voltage	230 V
Energy consumption	15 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	1800 lm (360°)
Luminous flux**	1600 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	150 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 +40 °
Lifespan	17000 h
Housing material	Plastic
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	596x46x63 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC

IP44

120
lm/W

Related documents

 Declaration of Conformity Photometric file

