

ORBITO

SLI043018WW_PW

Downlight luminaire ORBITO, with a power of 10 W, high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.




Power	10 W	Voltage	230 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	40 °	UGR	<19
IK	06	Degree of protection (IP)	IP44

Technical data


Code	SLI043018WW_PW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50-60 Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	1100 lm (360°)
Luminous flux**	800 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	1500 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	06
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	97x65 mm
Mounting hole	75 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

