





Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>10000 lm (90°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>60 °</b>
Protection class	<b>IP44</b>		



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI044012NW
Power	100 W
Nominal current	440 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	10000 lm (90°)
Luminous flux**	10000 lm (360°)
Light efficiency	100 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	60 °
RA	80
Light source included	+
Uniformity of color SDCM max	6
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Protection class	IP44
Colour	Black
Dimension (axbxc)	298x170 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
Luminaire available on request.