



Power **200 W**
Luminous flux* **30000 lm (90°)**
Light colour **Neutral white**
IK **07**

Voltage **230 V**
Colour temperature **4000 K**
Beam angle **90 °**
Protection class **IP65**



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI044013NW
Power	200 W
Nominal current	900 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	SOSEN
Power factor	0.98
Useful luminous flux*	30000 lm (90°)
Luminous flux**	30000 lm (360°)
Light efficiency	150 lm/W
Luminous intensity	16000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	07
Protection class	IP65
Colour	Black
Dimension (axbxc)	405x130 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux
For request available also version DALI.