



Power	100 W	Voltage	230 V
Luminous flux*	15500 lm (90°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	90 °
IK	07	Protection class	IP65



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI044015NW
Power	100 W
Nominal current	460 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.98
Useful luminous flux*	15500 lm (90°)
Luminous flux**	15500 lm (360°)
Light efficiency	155 lm/W
Luminous intensity	7800 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Light source included	+
Producer of LED diodes	PHILIPS
Uniformity of color SDCM max	5
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	07
Protection class	IP65
Colour	Black
Dimension (axbxc)	296 x 152 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux
For request available also version DALI