





Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>14700 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>90°</b>
UGR	<b>n/a</b>	IK	<b>10</b>



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI044017NW
Power	100 W
Nominal current	436 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	14700 lm (120°)
Luminous flux**	17000 lm (360°)
Light efficiency	170 lm/W
Luminous intensity	8100 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
UGR	n/a
RA	>80
Light source included	Yes
Dimmable	1-10V
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Protection class	IP66
Colour	Black
Dimension (axbxc)	263x110 mm
For use	Inside/Outside
Assembly method	Suspended
Whether it should work in conditions other than normal?	Yes
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux