





| | | | |
|----------------|-----------------------|--------------------|---------------|
| Power | 190 W | Voltage | 230 V |
| Luminous flux* | 20400 lm (90°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 90° |
| UGR | - | IK | 09 |



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|-----------------|
| Product code | SLI044021NW |
| Power | 190 W |
| Nominal current | 840 mA |
| Voltage | 230 V |
| Energy efficiency classe | E |
| Energy consumption | 190 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power factor | 0.9 |
| Useful luminous flux* | 20400 lm (90°) |
| Luminous flux** | 18000 lm (360°) |
| Light efficiency | 95 lm/W |
| Luminous intensity | 9300 cd |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 90 ° |
| UGR | - |
| RA | >80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum |
| IK | 09 |
| Protection class | IP66 |
| Colour | Black |
| Dimension (axbxc) | 353x114 mm |
| For use | Inside/Outside |
| Assembly method | Suspended |
| Application | Inside/Outside |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux