

PLATEO 4

SLI044029NW_PW

High bay luminaire PLATEO 4, with a power of 100/150/200 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK9 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 90° gives directional light so that selected surfaces can be better exposed. Designed for suspended mounting.



IP65

IK09



Power	100/150/200 W
Luminous flux*	31000 lm (360°)
Colour of light	Neutral white
IK	9

Voltage	230 V
Colour temperature	4000 K
Beam angle	90 °
Degree of protection (IP)	IP65

Technical data

Code	SLI044029NW_PW
Power	100/150/200 W
Nominal current	900 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.97
Useful luminous flux*	31000 lm (360°)
Luminous flux**	15000-23000-30000 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	13500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	0-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	9
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	280x145 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

