



Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2700 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI045003NW_PW
Power	18 W
Nominal current	130 mA
Voltage	230 V
Energy efficiency classe	D
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.7
Useful luminous flux*	2700 lm (360°)
Luminous flux**	2200 lm (360°)
Light efficiency	150 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	76x600x26 mm
For use	Inside
Assembly method	On the ceiling/Suspended
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux