

# VIGA

SLI045004NW\_PW

Linear luminaire VIGA, with a power of 28 W, high light efficacy 114 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for both surface and suspended mounting.



|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>28 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>3200 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Colour of light           | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP20</b>           |                    |               |

## Technical data

|                              |                           |
|------------------------------|---------------------------|
| Code                         | SLI045004NW_PW            |
| Power                        | 28 W                      |
| Nominal current              | 140 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 28 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | II                        |
| Power supply included        | +                         |
| Power factor                 | 0.9                       |
| Useful luminous flux*        | 3200 lm (360°)            |
| Luminous flux**              | 2600 lm (360°)            |
| Lamp efficacy                | 114 lm/W                  |
| Colour temperature           | 4000 K                    |
| Colour of light              | Neutral white             |
| Beam angle                   | 120 °                     |
| RA                           | 80                        |
| Uniformity of color SDCM max | 5                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 17000 h                   |
| Housing material             | PC                        |
| Degree of protection (IP)    | IP20                      |
| Colour                       | White                     |
| Dimension (AxBxC)            | 76x1200x26 mm             |
| For use                      | Inside                    |
| Assembly method              | On the ceiling, Suspended |
| Application                  | INT                       |
| Made in                      | PRC                       |

## Related documents



 User manual



 Declaration of Conformity



 Photometric file