


LIMEA SLIM 2 hermetic lamp



Power	36 W	Voltage	230 V
Luminous flux*	6000 lm (120°)	Colour of light	NW
Beam angle	120 °	UGR	22 lm
IK	08	Degree of protection (IP)	IP66



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI047006NW
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy efficiency class	C
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	6000 lm (120°)
Luminous flux**	5200 lm (360°)
Lamp efficacy	167 lm/W
Colour of light	NW
Beam angle	120 °
UGR	22
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	plastic
IK	08
Degree of protection (IP)	IP66
Colour	Gray/White
Dimension (AxBxC)	1700x65x67 mm
Weight	1.48 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Number of pieces on the packaging	12 pcs.
Made in	PRC
Other	L80B10 50000h MTBF 80000h straight-through conne-



*applies to the LED source used. **Luminaire luminous flux