



Power **75 W**

Voltage **230 V**

Colour temperature **4000 K**

Light colour **Neutral white**

Beam angle **90 °**

Protection class **IP40**



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| Product code                 | SLI047100NW_PW                                  |
| Power                        | 75 W                                            |
| Nominal current              | 335 mA                                          |
| Voltage                      | 230 V                                           |
| Energy consumption           | 75 kWh/1000h                                    |
| Frequency                    | 50HZ Hz                                         |
| Protection class             | I                                               |
| Power supply included        | +                                               |
| Power factor                 | 0.98                                            |
| Useful luminous flux*        | 13500 lm (360°)                                 |
| Luminous flux**              | 12750 lm (360°)                                 |
| Light efficiency             | 180 lm/W                                        |
| Colour temperature           | 4000 K                                          |
| Light colour                 | Neutral white                                   |
| Beam angle                   | 90 °                                            |
| RA                           | 80                                              |
| Uniformity of color SDCM max | 5                                               |
| Dimmable                     | DALI                                            |
| Working temperature range    | -20/+40 °                                       |
| Lifespan                     | 50000 h                                         |
| Housing material             | Aluminum/PC                                     |
| Protection class             | IP40                                            |
| Colour                       | White                                           |
| Dimension (axbxc)            | 1438x65x40 mm                                   |
| For use                      | Inside                                          |
| Assembly method              | On the ceiling/Suspended                        |
| Application                  | INTERNAL                                        |
| Made in                      | PRC                                             |
| Other                        | Max ilość opraw na zabezpieczenie nadprądowe: , |



\*Applies to the LED source used. \*\*Luminaire luminous flux