

ALLDAY BASIC CCT 3F

SLI047300CCT_PW_3F



Power	40 W	Voltage	230 V
Luminous flux*	5000 lm (360°)	Colour temperature	2700/4000/6000 K
Colour of light	CCT	Beam angle	115 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI047300CCT_PW_3F
Power	40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	5000 lm (360°)
Luminous flux**	4000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	115 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	1203x92x37 mm
For use	Inside
Assembly method	On the ceiling, zwieszany
Application	Inside
Made in	PL
Other	Funkcja zmiany barwy światła 2700K/4000K/6000K ,

