



Power **1 W**

Voltage **3.2 V**

Colour temperature **3000/4000/6000 K**

Light colour **CCT**


Protection class **IP65**



 User manual

#### Technical data:

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| Product code                 | SLI053001CCT                                     |
| Power                        | 1 W                                              |
| Voltage                      | 3.2 V                                            |
| Energy consumption           | 1 kWh/1000h                                      |
| Protection class             | III                                              |
| Luminous flux**              | 60 lm (360°)                                     |
| Colour temperature           | 3000/4000/6000 K                                 |
| Light colour                 | CCT                                              |
| RA                           | 80                                               |
| Uniformity of color SDCM max | 5                                                |
| Dimmable                     | No                                               |
| Working temperature range    | -20/+40 °                                        |
| Lifespan                     | 17000 h                                          |
| Housing material             | ABS+PC                                           |
| Protection class             | IP65                                             |
| Colour                       | Black                                            |
| Dimension (axbxc)            | 126x52 + 120 wspornik (3szt) + 180 wbijak mm     |
| For use                      | Outside                                          |
| Assembly method              | GRUNTOWY                                         |
| Application                  | EXT                                              |
| Made in                      | PRC                                              |
| Other                        | CCT function ,working time ~12h, charging 4-6h , |



\*Applies to the LED source used. \*\*Luminaire luminous flux