

HANGIT MULTIWAY S

WLD+20006

LED luminaire HANGIT MULTIWAY S, with a power of 11 W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Narrow beam angle 30° gives directional light so that selected objects or surfaces can be better exposed. Designed for surface mounting.



Power	11 W
Colour temperature	2700 K
Beam angle	30 °

Voltage	230 V
Colour of light	WW
Degree of protection (IP)	IP20

Technical data

Code	WLD+20006
Power	11 W
Nominal current	80 mA
Voltage	230 V
Energy consumption	11 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	1070 lm (360°)
Luminous flux**	600 lm (360°)
Lamp efficacy	97 lm/W
Luminous intensity	2200 cd
Colour temperature	2700 K
Colour of light	WW
Beam angle	30 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	48x400 + baza 80x115 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC

Logistics data

Bulk packaging	12 pcs.
Gross weight (1 pcs.)	1.1083 kg

Related documents

 User manual Declaration of Conformity Photometric file

