

SYSTEM SHIFT - GLOBE P

WLD+40001

On track luminaire SYSTEM SHIFT - GLOBE P, with a power of 5 W, high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.

Power **5 W**Colour temperature **3000 K**Beam angle **165 °**Voltage **48 V**Colour of light **WW**Degree of protection (IP) **IP20**


Technical data

| | |
|------------------------------|---------------------|
| Code | WLD+40001 |
| Power | 5 W |
| Nominal current | 100 mA |
| Voltage | 48 V |
| Energy consumption | 5 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 550 lm (360°) |
| Luminous flux** | 435 lm (360°) |
| Lamp efficacy | 110 lm/W |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 165 ° |
| RA | >90 |
| Light source included | Yes |
| Producer of LED diodes | osram |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 50000 h |
| Housing material | AL+PC |
| Degree of protection (IP) | IP20 |
| Colour | Czarny |
| Dimension (AxBxC) | 100 (850mm wire) mm |
| For use | Inside |
| Assembly method | NA SZYŃE |
| Application | Inside |
| Made in | PRC |




Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

