

# SYSTEM SHIFT - LINE M

WLD+40009

On track luminaire SYSTEM SHIFT - LINE M, with a power of 17 W, high light efficacy 106 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.



|                    |               |                           |             |
|--------------------|---------------|---------------------------|-------------|
| Power              | <b>17 W</b>   | Voltage                   | <b>48 V</b> |
| Colour temperature | <b>3000 K</b> | Colour of light           | <b>WW</b>   |
| Beam angle         | <b>100 °</b>  | Degree of protection (IP) | <b>IP20</b> |


## Technical data

|                              |                |
|------------------------------|----------------|
| Code                         | WLD+40009      |
| Power                        | 17 W           |
| Nominal current              | 350 mA         |
| Voltage                      | 48 V           |
| Energy consumption           | 17 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power factor                 | 1              |
| Useful luminous flux*        | 1800 lm (360°) |
| Luminous flux**              | 840 lm (360°)  |
| Lamp efficacy                | 106 lm/W       |
| Luminous intensity           | 285 cd         |
| Colour temperature           | 3000 K         |
| Colour of light              | WW             |
| Beam angle                   | 100 °          |
| RA                           | >90            |
| Light source included        | Yes            |
| Producer of LED diodes       | osram          |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20 to +40 °   |
| Lifespan                     | 50000 h        |
| Housing material             | AL+PC          |
| Degree of protection (IP)    | IP20           |
| Colour                       | Czarny         |
| Dimension (AxBxC)            | 602x23x42 mm   |
| For use                      | Inside         |
| Assembly method              | NA SZYŃĘ       |
| Application                  | Inside         |
| Made in                      | PRC            |




## Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

