

WLD+40013_SMART

WLD+40013_SMART



Power	22 W	Voltage	48 V
Colour temperature	3000/4000/6000 K	Colour of light	CCT
Beam angle	40 °	UGR	<19
Degree of protection (IP)	IP20		

Technical data






Code	WLD+40013_SMART
Power	22 W
Nominal current	450 mA
Voltage	48 V
Energy consumption	22 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	2250 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	102 lm/W
Luminous intensity	2150 cd
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	440x23x42 mm
For use	Inside
Assembly method	NA SZYBĘ
Application	Inside
Made in	PRC
Other	CCT/DIM ,



Related documents

[User manual](#)[Declaration of Conformity](#)



<p>48V </p>  <p>Die Montage erfolgt über ein einfaches Klick-System zusätzlich lässt sich die Leuchte je nach Bedarf verschieben</p>	<p>48V </p>  <p>Luminaire assembly within the track on "click" and its free arrangement</p>	
--	--	---

