

# SYSTEM SHIFT - LINE S

WLD+40037

On track luminaire SYSTEM SHIFT - LINE S, with a power of 8 W, high light efficacy 123 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.



|                    |               |
|--------------------|---------------|
| Power              | <b>8 W</b>    |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>100 °</b>  |

|                           |             |
|---------------------------|-------------|
| Voltage                   | <b>48 V</b> |
| Colour of light           | <b>WW</b>   |
| Degree of protection (IP) | <b>IP20</b> |

## Technical data

|                              |                         |
|------------------------------|-------------------------|
| Code                         | WLD+40037               |
| Power                        | 8 W                     |
| Nominal current              | 170 mA                  |
| Voltage                      | 48 V                    |
| Energy consumption           | 8 kWh/1000h             |
| Frequency                    | DC Hz                   |
| Protection class             | III                     |
| Power factor                 | 1                       |
| Useful luminous flux*        | 980 lm (360°)           |
| Luminous flux**              | 400 lm (360°)           |
| Lamp efficacy                | 123 lm/W                |
| Luminous intensity           | 135 cd                  |
| Colour temperature           | 3000 K                  |
| Colour of light              | WW                      |
| Beam angle                   | 100 °                   |
| RA                           | >90                     |
| Light source included        | Yes                     |
| Producer of LED diodes       | osram                   |
| Uniformity of color SDCM max | 5                       |
| Dimmable                     | No                      |
| Working temperature range    | -20 to +40 °            |
| Lifespan                     | 50000 h                 |
| Housing material             | AL+PC                   |
| Degree of protection (IP)    | IP20                    |
| Colour                       | White                   |
| Dimension (AxBxC)            | 304x23x42 mm            |
| For use                      | Inside                  |
| Assembly method              | NA SZYNOPROutsideÓD 48V |
| Application                  | Inside                  |
| Made in                      | PRC                     |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 50 pcs.   |
| Quantity per pallet   | 1200 pcs. |
| Gross weight (1 pcs.) | 0.23 kg   |

## Related documents

 User manual Declaration of Conformity Photometric file 3D model

