

# SYSTEM SHIFT NEON FLEX TUBE M

WLD+40058

On track luminaire SYSTEM SHIFT NEON FLEX TUBE M, with a power of 16 W, high light efficacy 103 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 360° ensures even illumination of the room. Designed to be mounted on a track.



|                    |               |
|--------------------|---------------|
| Power              | <b>16 W</b>   |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>360 °</b>  |

|                           |             |
|---------------------------|-------------|
| Voltage                   | <b>48 V</b> |
| Colour of light           | <b>WW</b>   |
| Degree of protection (IP) | <b>IP20</b> |

## Technical data

|                              |                          |
|------------------------------|--------------------------|
| Code                         | WLD+40058                |
| Power                        | 16 W                     |
| Nominal current              | 310 mA                   |
| Voltage                      | 48 V                     |
| Energy consumption           | 16 kWh/1000h             |
| Frequency                    | DC Hz                    |
| Protection class             | III                      |
| Power factor                 | 1                        |
| Useful luminous flux*        | 1640 lm (360°)           |
| Luminous flux**              | 1200 lm (360°)           |
| Lamp efficacy                | 103 lm/W                 |
| Colour temperature           | 3000 K                   |
| Colour of light              | WW                       |
| Beam angle                   | 360 °                    |
| RA                           | >90                      |
| Light source included        | Yes                      |
| Uniformity of color SDCM max | 5                        |
| Dimmable                     | No                       |
| Working temperature range    | -20 to +40 °             |
| Lifespan                     | 50000 h                  |
| Housing material             | SILIKON                  |
| Degree of protection (IP)    | IP20                     |
| Colour                       | White                    |
| Dimension (AxBxC)            | 22x1000 mm               |
| For use                      | Inside                   |
| Assembly method              | NA SZYNOPROOutsideÓD 48V |
| Application                  | Inside                   |
| Made in                      | PRC                      |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 20 pcs.  |
| Gross weight (1 pcs.) | 0.333 kg |

## Related documents

 User manual Declaration of Conformity Photometric file

