

SYSTEM SHIFT BASIC HANGIT CRISTAL

WLD+70015WW

On track luminaire SYSTEM SHIFT BASIC HANGIT CRISTAL, with a power of 6 W, high light efficacy 100 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 80° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	6 W
Colour temperature	3000 K
Beam angle	80 °

Voltage	48 V
Colour of light	WW
Degree of protection (IP)	IP20

Technical data

Code	WLD+70015WW
Power	6 W
Nominal current	120 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	600 lm (360°)
Luminous flux**	550 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	200 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	80 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	55x110 (1100mm wire) mm
For use	Inside
Assembly method	NA SZYŃ
Application	Inside
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file