

SYSTEM SHIFT BASIC GRID ADJUSTABLE

WLD+70016WW

On track luminaire SYSTEM SHIFT BASIC GRID ADJUSTABLE, with a power of 6 W, high light efficacy 100 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 24° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	6 W
Colour temperature	3000 K
Beam angle	24 °
Degree of protection (IP)	IP20

Voltage	48 V
Colour of light	WW
UGR	<19

Technical data

Code	WLD+70016WW
Power	6 W
Nominal current	100 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	600 lm (360°)
Luminous flux**	400 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	1700 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	24 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	110x23x110 mm
For use	Inside
Assembly method	NA SZYŃ
Application	Inside
Made in	PRC

Related documents



User manual



Declaration of Conformity



Photometric file