

SYSTEM SHIFT BASIC GRID M

WLD+70030NW

On track luminaire SYSTEM SHIFT BASIC GRID M, with a power of 18 W, high light efficacy 111 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 24° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	18 W	Voltage	48 V
Colour temperature	4000 K	Colour of light	Neutral white
Beam angle	24 °	UGR	<19
Degree of protection (IP)	IP20		

Technical data

Code	WLD+70030NW
Power	18 W
Nominal current	270 mA
Voltage	48 V
Energy consumption	18 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	2000 lm (360°)
Luminous flux**	1300 lm (360°)
Lamp efficacy	111 lm/W
Luminous intensity	5700 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	24 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	330x23x42 mm
For use	Inside
Assembly method	NA SZYNOPROutsideÓD 48V
Application	Inside
Made in	PRC

Logistics data

Bulk packaging	50 pcs.
Gross weight (1 pcs.)	0.18 kg

Related documents

 User manual Declaration of Conformity