

SYSTEM SHIFT BASIC GLOBE RING

WLD+70032NW

On track luminaire SYSTEM SHIFT BASIC GLOBE RING, with a power of 10 W, high light efficacy 130 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power **10 W**

Colour temperature **4000 K**

Beam angle **60 °**

Voltage **48 V**

Colour of light **Neutral white**

Degree of protection (IP) **IP20**

Technical data

| | |
|------------------------------|----------------|
| Code | WLD+70032NW |
| Power | 10 W |
| Nominal current | 200 mA |
| Voltage | 48 V |
| Energy consumption | 10 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 1300 lm (360°) |
| Luminous flux** | 300 lm (360°) |
| Lamp efficacy | 130 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 60 ° |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | AL+PC |
| Degree of protection (IP) | IP20 |
| Colour | Czarny |
| Dimension (AxBxC) | 90x150 mm |
| For use | Inside |
| Assembly method | NA SZYŃE |
| Application | Inside |
| Made in | PRC |

Related documents



 User manual



 Declaration of Conformity