

# SYSTEM SHIFT BASIC GLOBE RING PENDANT

WLD+70033NW

On track luminaire SYSTEM SHIFT BASIC GLOBE RING PENDANT, with a power of 10 W, high light efficacy 130 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power **10 W**

Colour temperature **4000 K**

Beam angle **60 °**

Voltage **48 V**

Colour of light **Neutral white**

Degree of protection (IP) **IP20**

## Technical data

---

Code	WLD+70033NW
Power	10 W
Nominal current	200 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1300 lm (360°)
Luminous flux**	300 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	90 (1200mm wire) mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC

## Related documents

---



 User manual



 Declaration of Conformity