

SYSTEM SHIFT BASIC GLOBE RING PENDANT

WLD+70049NW

On track luminaire SYSTEM SHIFT BASIC GLOBE RING PENDANT, with a power of 10 W, high light efficacy 130 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.




Power	10 W	Voltage	48 V
Colour temperature	4000 K	Colour of light	Neutral white
Beam angle	60 °	Degree of protection (IP)	IP20

Technical data


Code	WLD+70049NW
Power	10 W
Nominal current	200 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1300 lm (360°)
Luminous flux**	300 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	90 (1200mm wire) mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC

Related documents



 User manual



 Declaration of Conformity