

# LED STRIP

W0J+12209

LED strip LED STRIP 30 (9,6) W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier



|                           |                                 |                    |               |
|---------------------------|---------------------------------|--------------------|---------------|
| Power                     | <b>30 (9,6) W</b>               | Voltage            | <b>12 V</b>   |
| Luminous flux**           | <b>2700 (750) lm<br/>(360°)</b> | Colour temperature | <b>3000 K</b> |
| Colour of light           | <b>WW</b>                       | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP20</b>                     |                    |               |

## Technical data

---

|                              |                      |
|------------------------------|----------------------|
| Code                         | W0J+12209            |
| Power                        | 30 (9,6) W           |
| Nominal current              | 2500 mA              |
| Voltage                      | 12 V                 |
| Energy efficiency class      | G                    |
| Energy consumption           | 5 kWh/1000h          |
| Frequency                    | DC Hz                |
| Power supply included        | No                   |
| Power factor                 | 1                    |
| Luminous flux**              | 2700 (750) lm (360°) |
| Lamp efficacy                | 90 lm/W              |
| Colour temperature           | 3000 K               |
| Colour of light              | WW                   |
| Beam angle                   | 120 °                |
| RA                           | 90                   |
| Uniformity of color SDCM max | 5                    |
| Dimmable                     | Yes                  |
| Working temperature range    | -20/+40 °            |
| Lifespan                     | 50000 h              |
| Degree of protection (IP)    | IP20                 |
| Dimension (AxBxC)            | 8X5000 mm            |
| For use                      | Inside               |
| Application                  | INT                  |
| Made in                      | PRC                  |
| Other                        | 1m-800mA ,           |


## Related documents

---



 Declaration of Conformity



 Photometric file