

LED G4

WOJ+13118

LED source LED G4 1,5 W in silicone cover. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Wide beam angle 270° ensures even illumination of the room.



Power	1,5 W	Voltage	12 V
Luminous flux**	110 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	270 °
Socket	G4		

Technical data

Code	W0J+13118
Power	1,5 W
Nominal current	80 mA
Voltage	12 V
Energy efficiency class	G
Energy consumption	2 kWh/1000h
Frequency	50HZ Hz
Power factor	0,4
Useful luminous flux*	110 lm (360°)
Luminous flux**	110 lm (360°)
Lamp efficacy	73 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	G4
Dimension (AxBxC)	∅9,5x36 mm
For use	Inside
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity

