

# LED GU10

WOJ+14104

LED source LED GU10 6 W with the popular GU10 socket and classic shape. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 10° gives directional light so that selected objects or surfaces can be better exposed.



---

|                 |                      |                           |               |
|-----------------|----------------------|---------------------------|---------------|
| Power           | <b>6 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux** | <b>480 lm (360°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b> | Beam angle                | <b>10 °</b>   |
| Socket          | <b>GU10</b>          | Degree of protection (IP) | <b>IP20</b>   |

---

## Technical data


---

|                              |               |
|------------------------------|---------------|
| Code                         | WQJ+14104     |
| Power                        | 6 W           |
| Nominal current              | 50 mA         |
| Voltage                      | 230 V         |
| Energy efficiency class      | G             |
| Energy consumption           | 6 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0,5           |
| Useful luminous flux*        | 390 lm (90°)  |
| Luminous flux**              | 480 lm (360°) |
| Lamp efficacy                | 65 lm/W       |
| Luminous intensity           | 2700 cd       |
| Colour temperature           | 4000 K        |
| Colour of light              | Neutral white |
| Beam angle                   | 10 °          |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Socket                       | GU10          |
| Degree of protection (IP)    | IP20          |
| Dimension (AxBxC)            | 50x58 mm      |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |


## Related documents

---



 Declaration of Conformity



 Photometric file