

LED MR11 GU10

WOJ+14158

LED source LED MR11 GU10 2 W with the popular GU10 mount. It is characterised by a high light efficacy 115 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 45° gives directional light so that selected objects or surfaces can be better exposed.




Power	2 W	Voltage	230 V
Luminous flux**	230 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	45 °
Socket	GU10		

Technical data

Code	W0J+14158
Power	2 W
Nominal current	20 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	2 kWh/1000h
Frequency	50HZ Hz
Power factor	0.4
Useful luminous flux*	165 lm (90°)
Luminous flux**	230 lm (360°)
Lamp efficacy	115 lm/W
Luminous intensity	220 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	45 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	GU10
Dimension (AxBxC)	35x48 mm
For use	Inside
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file