

LED PAR30

WOJ+14174

LED source LED PAR30 20 W with E-27 base and with a 'candle' shape'. It is characterised by a high light efficacy 100 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Narrow beam angle 24° gives directional light so that selected objects or surfaces can be better exposed.



Power	20 W	Voltage	230 V
Luminous flux**	2000 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	24 °
Socket	E27	Degree of protection (IP)	IP20

Technical data

Code	WOJ+14174
Power	20 W
Nominal current	95 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Power supply included	+
Power factor	0.5
Useful luminous flux*	2000 lm (90°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	3000 cd
Colour temperature	6000 K
Colour of light	CW
Beam angle	24 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	E27
Degree of protection (IP)	IP20
Dimension (AxBxC)	95 x 130 mm
For use	Inside
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file