



---

|                 |                      |
|-----------------|----------------------|
| Power           | <b>8 W</b>           |
| Luminous flux** | <b>750 lm (360°)</b> |
| Light colour    | <b>CW</b>            |
| Base            | <b>E-14</b>          |

|                    |               |
|--------------------|---------------|
| Voltage            | <b>230 V</b>  |
| Colour temperature | <b>6000 K</b> |
| Beam angle         | <b>160 °</b>  |

---



 Declaration of Conformity

**Technical data:**

|                              |               |
|------------------------------|---------------|
| Product code                 | WOJ+14222     |
| Power                        | 8 W           |
| Nominal current              | 70 mA         |
| Voltage                      | 230 V         |
| Energy efficiency classe     | F             |
| Energy consumption           | 8 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0.5           |
| Useful luminous flux*        | 680 lm (360°) |
| Luminous flux**              | 750 lm (360°) |
| Light efficiency             | 85 lm/W       |
| Colour temperature           | 6000 K        |
| Light colour                 | CW            |
| Beam angle                   | 160 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | -             |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Base                         | E-14          |
| Dimension (axbxc)            | 37x107 mm     |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |

