



---

|                  |                             |                    |               |
|------------------|-----------------------------|--------------------|---------------|
| Power            | <b>24(5,6) W</b>            | Voltage            | <b>12 V</b>   |
| Luminous flux**  | <b>2000 (490) lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour     | <b>Neutral white</b>        | Beam angle         | <b>120 °</b>  |
| Protection class | <b>IP44</b>                 |                    |               |

---



 Declaration of Conformity

**Technical data:**

|                              |                         |
|------------------------------|-------------------------|
| Product code                 | WOJ+14423               |
| Power                        | 24(5,6) W               |
| Nominal current              | 1500 mA                 |
| Voltage                      | 12 V                    |
| Energy efficiency classe     | G                       |
| Energy consumption           | 6 kWh/1000h             |
| Frequency                    | DC Hz                   |
| Power factor                 | 1                       |
| Luminous flux**              | 2000 (490) lm (360°)    |
| Light efficiency             | 83 lm/W                 |
| Colour temperature           | 4000 K                  |
| Light colour                 | Neutral white           |
| Beam angle                   | 120 °                   |
| RA                           | 90                      |
| Uniformity of color SDCM max | 5                       |
| Dimmable                     | +                       |
| Working temperature range    | -20/+40 °               |
| Lifespan                     | 17000 h                 |
| Protection class             | IP44                    |
| Dimension (axbxc)            | 8x20000 mm              |
| For use                      | Inside/Outside          |
| Application                  | INT/EXT                 |
| Made in                      | PRC                     |
| Other                        | 0,5m-230mA, 1m -460mA , |

