




| | | | |
|------------------|------------------------------|--------------------|--------------------|
| Power | 115 (18,4) W | Voltage | 24 V |
| Luminous flux** | 9300 (1290) lm (360°) | Colour temperature | 3000-6000 K |
| Light colour | CCT | Beam angle | 120 ° |
| Protection class | IP20 | | |



 Declaration of Conformity

Technical data:

| | |
|------------------------------|-----------------------|
| Product code | WOJ+14491 |
| Power | 115 (18,4) W |
| Nominal current | 5000 mA |
| Voltage | 24 V |
| Energy efficiency classe | F |
| Energy consumption | 122 kWh/1000h |
| Frequency | DC Hz |
| Useful luminous flux* | 9300 lm (120°) |
| Luminous flux** | 9300 (1290) lm (360°) |
| Light efficiency | 81 lm/W |
| Colour temperature | 3000-6000 K |
| Light colour | CCT |
| Beam angle | 120 ° |
| RA | >90 |
| Uniformity of color SDCM max | 5 |
| Dimmable | Yes |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Protection class | IP20 |
| Dimension (axbxc) | 10x5000 mm |
| For use | Inside |
| Made in | PRC |
| Other | 3000-6000K , |

