

LED GLS

W0J+14628

Smart light bulb Bluetooth Mesh, LED source GLS with possibility to change the colour of the light (RGB), with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via remote control, light switch and app on your mobile device. It is an LED source, a light bulb with E-27 base and with the shape of a traditional light bulb. It is characterised by a high light efficacy 110 lm/W



| | | | |
|-----------------|----------------------|---------------------------|--------------------|
| Power | 8,5 W | Voltage | 230 V |
| Luminous flux** | 940 lm (360°) | Colour temperature | 2700-6500 K |
| Colour of light | CCT/RGB | Beam angle | 220 ° |
| Socket | E27 | Degree of protection (IP) | IP20 |

Technical data

| | |
|------------------------------|--------------------|
| Code | W0J+14528 |
| Power | 8,5 W |
| Nominal current | 60 mA |
| Voltage | 230 V |
| Energy efficiency class | E |
| Energy consumption | 9 kWh/1000h |
| Frequency | 50HZ Hz |
| Power supply included | + |
| Power factor | 0.7 |
| Useful luminous flux* | 940 lm (360°) |
| Luminous flux** | 940 lm (360°) |
| Lamp efficacy | 110 lm/W |
| Colour temperature | 2700-6500 K |
| Colour of light | CCT/RGB |
| Beam angle | 220 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | SMART |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Socket | E27 |
| Degree of protection (IP) | IP20 |
| Dimension (AxBxC) | 60x117 mm |
| Made in | PRC |
| Other | RGBW(2700-6500K) , |

Related documents



 Declaration of Conformity

