

## ALLDAY 7 ASYMETRIC




---

Power	<b>55 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>60 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 Declaration of Conformity

ALD7PRO55830CLW

Technical data:

Code	WOJP03409
Power	55 W
Nominal current	263 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	55 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	8250 lm (360°)
Luminous flux**	4675 lm (360°)
Lamp efficacy	150 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	60 °
RA	80
Light source included	+
Producer of LED diodes	OSRAM
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	37x1145x115 mm
Weight	2.52 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux