




---

Power	<b>80 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>4000 K</b>	Colour of light	<b>Neutral white</b>
Beam angle	<b>75 °</b>	Degree of protection (IP)	<b>IP20</b>

---




 Declaration of Conformity

ALD7PR080840SMW

**Technical data:**

Code	WOJP03419
Power	80 W
Nominal current	382.6 mA
Voltage	230 V
Energy consumption	80 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	12000 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	150 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	75 °
RA	80
Light source included	+
Producer of LED diodes	OSRAM
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	37x1705x115 mm
Weight	3.24 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux